



Continuous duty high service factor electrical motor.

Failsafe motor brake reliably holds the lift in position. This brake prevents backdriving, even when the power is out.

Heavy gauge, high torque capacity drive tube with Gatorshield electroplating to prevent corrosion.

Engineered tribopolymer shaft bearings are lubrication and corrosion free. High load capacity provides industry best durability. These no maintenance bearings reduce service costs.

Roller cable keepers prevent snarl and overlap.

High torque capacity sprockets welded directly to the drive shaft.

3-1/2" diameter cable friendly grooved winder extends cable life. Grooves ensure proper cable winding.

Industrial duty gearless cycloidal drive is the most durable and efficient drive available in the boat lift industry. The Superlift is the fastest lift per horsepower. Up to 34,000 in-lbs of output torque.

Industrial grade ANSI roller chain for heavy duty power transmission. High shock load capability.

6061-T6 marine grade corrosion resistant aluminum and stainless steel construction with 15 year structural warranty.

Rugged cast aluminum weather resistant cover encloses the drive components, protecting them from the harsh marine elements.

Custom extruded top beam stepped channels provide structural support for the bearing blocks.

Heavy duty reinforced guide post base with pvc covered guide posts that are easily adjustable.

Maintenance free aluminum pulleys with self-lubricating bearings.

Custom extruded aluminum bunks with UV resistant non marring pvc cover.

T302/304 stainless steel cables with 6x37 construction for maximum flexibility and highest service life.